

STEP LIGHTS



SL65-LED
4" Integrated LED Edge Light

SL75-LED
7" Integrated LED Edge Light

SL85-LED
12" Integrated LED Edge Light

SL200
6" Louvered
Recessed Box Mount

SL300
9.5" Louvered
Recessed Box Mount

SL25-bt
SL25-LED
Integrated Surface Mount

SL35-bt
SL35-LED
Integrated Surface Mount



SL50
5" Ledge Light
SL50-bt

SL100
3.75" Puck Light



SL60-bt
5" Surface Mounted bt Ledge Light

SL150
Bell Light



TAPE-LED-5FT
5 Foot LED Tape Light
Can Be Cut To Size

TAPE-LED-15FT
15 Foot LED Tape Light
Can Be Cut To Size

TAPE-LED-15FT-LL
Lower Lumen Output

TAPE-LED-30FT
30 Foot LED Tape Light
Can Be Cut To Size



FLOOD LIGHTS



FL50
Bipin/G4
FL50-bt



FL100
Bipin/G4



FL200
MR16
FL200-bt
LED-6W
LED-5W
LED-4W

WALL SCONCES

WS100
3 inches



WS200
6 inches



WS300
MR16



LED-6W
LED-5W
LED-4W

WELL LIGHTS



WL100
PAR36
LED-10W
LED-8W
LED-4W



WL200
PAR36
WL200-bt
LED-10W
LED-8W
LED-4W



WL300
MR16
LED-6W
LED-5W
LED-4W



CGWL01
PAR36
LED-10W
LED-8W
LED-4W

POST LIGHT



POST100
MR16
LED-6W
LED-5W
LED-4W

IN-GROUND LIGHTS



GL100
MR16
Angled Shroud
GL100-bt
LED-6W
LED-5W
LED-4W



GL150
MR16
Flat Lens
GL150-bt
LED-6W
LED-5W
LED-4W



GL160
MR16
Grated Top
GL160-bt
LED-6W
LED-5W
LED-4W



GL170
MR16
Opposing Sides
GL170-bt
LED-6W
LED-5W
LED-4W



GL180
MR16
180° Output
GL180-bt
LED-6W
LED-5W
LED-4W



GL190
MR16
360° Output
GL190-bt
LED-6W
LED-5W
LED-4W

GL100 SERIES TOPS



GL300 SERIES TOPS



GL300
MR16
Flat Lens
GL300-bt
LED-6W
LED-5W
LED-4W



GL310
MR16
Domed Top
GL310-bt
LED-6W
LED-5W
LED-4W



GL350
MR16
Angled Shroud
GL350-bt
LED-6W
LED-5W
LED-4W



GL360
MR16
Grated Top
GL310-bt
LED-6W
LED-5W
LED-4W



GL370
MR16
Opposing Sides
GL370-bt
LED-6W
LED-5W
LED-4W



GL380
MR16
180° Output
GL380-bt
LED-6W
LED-5W
LED-4W



GL390
MR16
360° Output
GL390-bt
LED-6W
LED-5W
LED-4W

FIXTURE ACCESSORIES

PERMAPOST
Heavy Duty Ground Stake



RMB
Round Mounting Base



GUTTERMOUNT



TRANSFORMER ACCESSORIES

PC
Photocell with
Swivel Mount



TIMER
Mechanical Timer



A-LOC-50
Waterproof Interlocking
Wire Connectors



T-ADAPTER
"T" Shaped Extension



L-ADAPTER
"L" Shaped Extension



bt-RE

bt Range Extender

Features:

- Cast brass housing, aged brass finish
- 5 db external antenna
- LED network indicator light
- 10 Foot wire lead, 18 awg (UL listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Plastic ground stake (8.5 in, 21.6 cm length)
- Ten year warranty

Get Your Fixtures Talking!

The bt system uses Bluetooth Mesh technology to communicate. The mesh network becomes stronger with more devices in the same network. A distance gap between fixtures can cause a loss of communication. To ensure that all of your fixtures communicate with each other, install a bt Range Extender to each network on every job no matter how big or small.

Install the bt-RE on every bt job.

ALLIANCE


OUTDOOR LIGHTING

Since 2006

2022 PRODUCT GUIDE

LED LAMPS

 50w Halogen Equivalent	 35w Halogen Equivalent	 20w Halogen Equivalent
410 LUMENS (6W) MR16	310 LUMENS (5W) MR16	250 LUMENS (4W) MR16
LMR16-LED-6W-F 45° Flood, Enclosed Housing LMR16-LED-6W-2700K 2700K Color Temperature	LMR16-LED-5W-F 45° Flood LMR16-LED-5W-2700K 2700K Color Temperature LMR16-LED-310LM Enclosed Housing LMR16-LED-5W-WF 60° Wide Flood LMR16-LED-5W-NS 15° Narrow Spot	LMR16-LED-4W-F 45° Flood LMR16-LED-4W-2700K 2700K Color Temperature LMR16-LED-250LM Enclosed Housing LMR16-LED-4W-WF 60° Wide Flood LMR16-LED-4W-NS 15° Narrow Spot
 20w Halogen Equivalent	*All LED are 2900K Warm White and have an 8v to 24v operating range.	
175 LUMENS (4W) MR11		
LMR11-LED-4W-F 45° Flood		

 2.5 watt, 200 Lumens	 2.5 watt, 200 Lumens	 2.5 watt, 200 Lumens
BIPIN/G4 BASED	BAYONET BASED	WEDGE BASED
LBIPIN-LED-200LM 2.5 watt, 200 Lumens LBIPIN-LED-250LM 3 watt, 250 Lumens LBIPIN-LED-350LM 3.5 watt, 350 Lumens	LBA15S-LED-200LM 2.5 watt, Single Bayonet, 200lm LBA15D-LED-200LM 2.5 watt, Double Bayonet, 200lm	L3156-LED-200LM 2.5 watt, 3156 Wedge, 200 Lumens L3156-LED-250LM 3 watt, 3156 Wedge, 250 Lumens L921T5-LED-200LM 2.5 watt, T5 Wedge, 200 Lumens
*All Tower LED have an IP67 rating, 2700K warm white output and an 8v to 24v operating range. IP67: Lamps are dust tight and can be submerged in up to one meter of water.		

PAR36 DROP-IN LED LAMPS

			
400 LUMENS	300 LUMENS	250 LUMENS	BT DROP-IN
LPAR36-LED-10W-WF 10 watt, 40° LPAR36-LED-10W-F 10 watt, 30°	LPAR36-LED-8W-WF 8 watt, 40° LPAR36-LED-8W-F 8 watt, 20°	LPAR36-LED-4W-WF 4 watt, 40° LPAR36-LED-8W-F 4 watt, 20°	LPAR36-LED-BT 2-7 watts, 280-450lm 45° Flood
*All PAR36 LED have an IP66 rating, 2800K warm white output and an 9v to 24v operating range. IP66: Lamps are dust tight and can withstand powerful water jets from any direction.			

BULLET LIGHTS

 Small MR11	 MR16
BL50 LED-4W	BL110 LED-6W LED-5W LED-4W
 MR16	 PAR36
BL200 LED-6W LED-5W LED-4W	BL300 LED-10W LED-8W LED-4W
 Integrated LED	 MR16
BL400-bt	BL900 LED-6W LED-5W LED-4W

UNDERWATER LIGHTS

 MR16	 Includes Antenna
UL100 LED-6W LED-5W LED-4W	UL100-bt

AREA LIGHT HATS

 6.75"	 6.25"
AL100	AL150
 7.75"	 6.25"
AL250	AL300
 7.5"	 5"
AL400	AL500
 3.5"	
AL550	TIKI

COMMERCIAL GRADE HATS

 8.5"	 9"
AL700	AL750
 12"	 8"
AL800	AL850

AREA LIGHT STEMS

 60" Includes a PERMAPOST	 18" to 29" Adjustable Area Light Stem
ALSTEM60	ALSTEMADJ
 24"	 18"
ALSTEM24	ALSTEM18 ALSTEM18-bt
 12"	
ALSTEM12 ALSTEM12-bt	


PATH LIGHTS

 Fully Adjustable Hat	 Adjustable Stem	 Adjustable Stem
PL100 PL100-bt	PL200	PL250
 Contemporary Path Light	 Putting Green Light	
PL300-bt	GOLF100	

BOLLARD LIGHT

 29.5" Bollard 6" Hat
BOLLARD100
Includes mounting hardware

DOWN LIGHTS

 Small MR11	 MR16 Hanging
DL50 LED-4W	HL100 LED-6W LED-5W LED-4W
 MR16	 Bipin/G4 Hanging
DL100 LED-6W LED-5W LED-4W	HL200 LED-6W LED-4W
 MR16	
DL200 LED-6W LED-5W LED-4W	


it TRANSFORMERS Intelligent Transformers

 150 Watt Transformer, Two 14V Taps, Two Commons Bluetooth Ready Phone App Driven Astronomical Timer Multiple Taps DOE Compliant FOR LED ONLY	 300 Watt Transformer, Three 14V Taps, Three Commons Bluetooth Ready Phone App Driven Astronomical Timer Multiple Taps DOE Compliant FOR LED ONLY
IT150	IT300

XF TRANSFORMERS Multiple Volts (12 to 18)

	
XF150	XF300
XF600	
Two Common Lug Terminals Multiple Voltage Taps Stainless Steel Enclosure Lifetime Warranty	

TF TRANSFORMERS

 200 Watt Transformer, Two 12 Volt Taps Built In Photocell/Timer DOE Compliant	 300 Watt Transformer, Multi Tap (12 and 14 Volts) Built In Photocell/Timer DOE Compliant
TF200	TF300

bt family does it all

DOWNLOAD THE BT APP

App Store
IOS QR Code

Google Play
Android QR Code

- Change color temperatures
- Dim
- Group
- Change RGB colors
- Create custom scenes for holidays and events
- Create secured networks
- Phone app driven

Bluetooth

